


Professional Products    Medical    Monitors    Surgical Monitors  
43-inch 4K 2D HDR Medical Monitor LMD-43M1MD - Son...



LMD-43M1MD

42.5-inch 4K 2D Mini LED surgical monitor featuring Sony’s Advanced Local Dimming Technology (Backlight Master Drive)

*42.5-inch : 1079.9mm viewable area, measurement diagonally*

[Screen images on this page are simulated for illustrative purposes.]



Backlight Master Drive

Contact us

Where to buy

# LMD-43M1MD


Overview   Features   Specifications   Accessories   Resources

## New Standard of Brightness and Contrast


The LMD-43M1MD is the surgical monitor certified with VESA [DisplayHDR](#) 1000. Its extremely high peak luminance of 2,000 cd/m<sup>2</sup> and contrast ratio of 1,000,000:1 are achieved by Sony's advanced Local Dimming Technology (Backlight Master Drive), providing exceptional visual clarity that's essential for minimal invasive surgery. The unique Anti-Reflection Technology combines Low-Reflection and Anti-Glare surface treatment to minimise on-screen reflections in brightly-lit Operating Rooms.



Local Dimming OFF  
All LED ON



Local Dimming ON




# Experience Exceptional Clarity and Visual Detail

Sony’s advanced Local Dimming Technology (Backlight Master Drive) precisely controls the panel backlight’s dense array of mini LEDs to ensure stunning brightness and high contrast. LED backlighting sources are independently controlled in light and dark zones of the image. This significantly improves black reproduction by turning off LEDs, simultaneously using saved energy to boost peak brightness in highlight areas. This allows the LMD-43M1MD to achieve a peak brightness exceeding 2,000 cd/m<sup>2</sup>, and a contrast ratio of 1,000,000:1.

## Wide Colour Gamut for Realistic Visualisation

The LCD and signal processing technology employed in the LMD-43M1MD achieves a wide colour gamut conforming to ITU-R recommendation BT.2020. This allows for superior colour reproduction to achieve more realistic visualization of surgical images.









### Clarity in Light and Dark Areas

HDR technology offers surgeons a clearer view by visualising a wider range of brightness levels within the same scene, minimising the loss of fine detail in shadowed areas and overexposed highlights. The LMD-43M1MD can reproduce greater details enhanced by HDR when receiving and selecting HLG (Hybrid Log-Gamma) or PQ (Perceptual Quantization) signals.




### Minimised Screen Reflection in Brightly-lit Operating Rooms

Sony’s unique Anti-Reflection Technology featured in the LMD-43M1MD combines two reflection suppression technologies. Low Reflection reduces the amount of reflected light and minimises reflection from external light sources. This is reduced further by an Anti-Glare surface treatment that diffuses incoming light. By creating a slightly rough surface on the display, this Anti-Glare

surface maximises the diffusion of incoming light and minimises reflections. By combining these advanced surface treatment technologies, the LMD-43M1MD achieves a balance of diffusing incoming light, reducing reflections and minimising glare – ensuring extremely high contrast images with lifelike colour reproduction.

## Fanless Design Minimises Airflow Disruption


The LMD-43M1MD features a fanless cooling system that significantly minimises unwanted interference with ventilation airflow around the monitor.



Conventional monitor with cooling fan inside



LMD-32M1MD with fanless design  
less affect to airflow





## Intuitive Navigation and Custom Buttons

The monitor’s LED backlighting selectively illuminates active control buttons on the front panel, offering clear guidance to clinical staff even in dark environments. In addition frequently used functions can be assigned to three custom buttons on the front panel, allowing quick access and supporting enhanced workflow efficiency.

## Auto Panel Brightness Adjustment to Match Lighting Levels

The LMD-43M1MD is equipped with a built-in light sensor that automatically adjusts panel brightness to match changing ambient lighting conditions in the Operating Room. This ensures visibility even in cases during procedures like ICG navigation surgery, where darker room lighting is required.






## Suitable Design for Medical Facilities

The monitor’s smooth surface and streamlined back shape simplify cleaning of the entire monitor. Simple integration in the OR is assisted by the monitor’s slim bezel and rounded corners. The front of the LMD-43M1MD carries a splash proof and dust resistant rating of IP45, with an IP32 rating for the entire monitor.


## Installation-Friendly Cabling

Two cable access points with integral covers broaden installation options with easy cable management. AC power and HDMI cable holders ensure placement of cables, helping to prevent accidental disconnections.



## Versatile Connectivity Options

The LMD-43M1MD offers a comprehensive array of input/output connectors, including 12G-SDI, HDMI and Display Port. A USB 5V/1.5A (Type C) port provides power to connected external equipment. There’s also a USB (Type A) port that can be used to export/import monitor setting information from one monitor to another via the USB device.




## Multi-Image Display (PIP/POP)



The LMD-43M1MD offers a two-screen PIP/POP display function, allowing display of multi-information on one screen. Each input source can be displayed separately, with individual gamma values assigned.



Picture-in-Picture (PIP)



Picture-out-Picture (POP)



For example, endoscope :  
gamma value of 2.2, X- ray : DICOM




Off : Normal



180 degree Rotation



Mirror




Optimal Viewing Angles

The displayed image can be rotated 180 degrees or flipped horizontally. This ensures optimal viewing for surgeons and clinical teams in the OR, regardless of the orientation of a connected endoscopic camera.

## Simplified Configuration of Multiple Monitors

The USB (Type A) port allows for monitor configuration settings to be stored to an attached USB device. This stored setting information can then be easily applied to other monitors via the USB device.



## Environmentally Conscious Efforts

The packaging for the LMD-43M1MD eliminates expanded polystyrene form, relacing it with molded pulp materials. The monitor is also supplied in a covered non-woven bag made mainly from plant cellulose. This reduces the amount of virgin plastic used for packaging.

## Power Saving

The LMD-43M1MD is equipped with the Sleep Mode function that contributes to a more energy-efficient use. When it is set to ON, the monitor enters into Power Saving mode by turning off the backlight if there is no input signal from the selected connector for more than 1 minute.



## Gallery



# Specifications

Expand all  Collapse all 

Picture Performance	
Input	
Output	
Input/Output	
General	
Supplied Accessories	

# Accessories



## NUA-BK30

IP Converter Bracket for NU-IP3R



# Related products



**LMD-XH550MT**  
55-inch 4K 3D/2D LCD medical monitor



**LMD-XH320MT**  
32-inch 4K 3D/2D LCD medical monitor



**LMD-XH550MD**  
55-inch 4K 2D surgical monitor



Support

Support

Manuals

Questions &  
Answers

Change Country, Region or Language

- Discover
- Technology
- Events
- Case Studies
- Press Centre

- Login/Register
- Channel Partners
- Alliances

- Get In Touch
- Contact us
- Press Contacts



[About us](#) | [Modern Slavery Act](#) | [Privacy](#) | [Website Accessibility](#) | [Site Map](#) | © 2004 - 2025 Sony Europe B.V. - [Terms and Conditions of Website Use](#)